



technical data sheet

long life exterior upvc rubber masking tape



description

upvc film backing with solvent rubber adhesive

Product Codes: GTA-C24, C36 & C48

specifications

backing
upvc film

adhesive
rubber

total thickness
0.145mm

adhesion to steel
5n/25mm

standard sizes
18,24,36,48mm x 50m

benefits

clean lines
clean removal
good uv resistance

tensile strength
110n/25mm

elongation
8%

temp resistance
60°c (30mins)

colours
blue

custom slit
up to 1410m

areas of use

long life exterior
painting applications



technical data sheet

conditions of use

for best results apply self adhesive tapes between 15°C and 25°C in a dry environment. application surfaces must be dry and free from dust and particles. do not apply on surfaces treated or contaminated by anti-adhesives. do not use paint containing additives which could reduce the adhesive properties. avoid contact with surfaces containing plasticizers or other chemical agents not compatible with the tape. in cases of rough or irregular surfaces, it is better to use a tape with a higher quantity of adhesive. care must be taken with reference to removability without residue and working conditions of the self adhesive tape.

tape storage

suggested storage temperature shall range between 15°C and 25°C with maximum relative humidity of 65%. material shall be stored away from heat sources and possible kept in the original package, avoiding light exposure as well. when temperatures are lower than suggested, it is always required to recondition the adhesive tape to normal temperatures before use.

tape shelf life

self-adhesive tapes technical features are generally not permanent but remain at their best for a minimum of 12 months, if stored according to suggested conditions and avoiding extreme environmental conditions such as quick and sudden temperature changes, extremely high or low temperatures, high levels of humidity, etc.

the information provided is based on our experience and tape industry knowledge. it is given in goodwill but is not intended as a guarantee or warranty. all end users should ensure themselves that the product is suitable for their own particular application before using.