

technical data sheet

professional painters crepe rubber masking tape



description

70g/m2 green staurated crepe paper with natural rubber adhesive

Product Codes: GTA-G24, G36 & G48

specifications

backing
crepe paper

tensile strength
87.5n/25mm

adhesive
rubber

elongation
8%

total thickness
0.130mm

temp resistance
80°C (30mins)

adhesion to steel
4.8n/25mm

colours
green

standard sizes
18,24,36,48mm x 50m

custom slit
up to 1410mm

benefits

clean lines
no residue
waterproof backing

areas of use

indoor masking
applications
automotive masking



technical data sheet

conditions of use

for best results apply self adhesive tapes between 15°C and 25°C in a dry environment. application surfaces must be dry and free from dust and particles. do not apply on surfaces treated or contaminated by anti-adhesives. do not use paint containing additives which could reduce the adhesive properties. avoid contact with surfaces containing plasticizers or other chemical agents not compatible with the tape. in cases of rough or irregular surfaces, it is better to use a tape with a higher quantity of adhesive. care must be taken with reference to removability without residue and working conditions of the self adhesive tape.

tape storage

suggested storage temperature shall range between 15°C and 25°C with maximum relative humidity of 65%. material shall be stored away from heat sources and possible kept in the original package, avoiding light exposure as well. when temperatures are lower than suggested, it is always required to recondition the adhesive tape to normal temperatures before use.

tape shelf life

self-adhesive tapes technical features are generally not permanent but remain at their best for a minimum of 12 months, if stored according to suggested conditions and avoiding extreme environmental conditions such as quick and sudden temperature changes, extremely high or low temperatures, high levels of humidity, etc.

the information provided is based on our experience and tape industry knowledge. it is given in goodwill but is not intended as a guarantee or warranty. all end users should ensure themselves that the product is suitable for their own particular application before using.